

Since 1898
CONSEW®

MODELS 701/702

701LP- LEFT POST AVAILABLE

WITH
 VERTICAL AXIS ROTARY HOOKS
 INTERMITTENT WHEEL FEED
 INTERMITTENT POSITIVELY DRIVEN
 ROLLER PRESSER
 SIMPLIFIED SEMI-AUTOMATIC LUBRICATION
 ANTI-FRICTION BALL AND ROLLER BEARINGS
 BUILT-IN BOBBIN WINDER



Model 701
 Single Needle



Model 702
 Two Needle

HIGH SPEED
 SINGLE AND TWO-NEEDLE
 POST BED LOCKSTITCH MACHINES
 DROP FEED, NEEDLE FEED
 POSITIVELY DRIVEN ROLLER PRESSER

POST BED

Models 701 / 702

APPLICATIONS

- Lower and driven presser wheel feeding action combined with needle feed provide powerful transport for slippery materials of any type as well as leather, vinyl and polyethylene plastics, oil cloth, just any material difficult to feed, coated and laminated fabrics.
- Suitable for stitching hollow, tubular and curved articles and climbing over thick sections always assuring constant stitch length.

FEATURES

- As many as 29 anti-friction ball and needle roller bearings (depending on model) for easy maintenance.
- Continuous lubrication from copious reservoir.
- Vertical axis rotating hooks.
- Triple feeding mechanism assures even feeding of difficult-to-sew materials.

AVAILABLE MODELS

701 - Single needle, lower wheel feed, driven upper wheel feed, needle feed

702 - Two needle, all other features same as Model 701

701LP - Left hand post

701U - Same as basic model, modified for maximum stitch length up to 21/64 (8mm)

701X - Same as basic model, modified for very heavy thread

701UX - Same as basic model, modified for maximum stitch length and heavy thread

701ATCL - Fitted with automatic thread trimmer and presser lift

702ATCL - Fitted with automatic thread trimmer and presser lift

SPECIFICATIONS

	Model 701	Model 702
Speed, Max. (S.P.M.)*	3500	
Clearance Under Foot	9/32" (7mm)	
Needle Bar Stroke	1 1/2" (38mm)	
Stitch Length, Max. (s.p.i.)	5 (5 mm)	6 (4 mm)
Needle	135 x 7 (cat. 1955)	
Bobbin	38033	
Metal		
Pre-wound	G	
Hook	38032	
Bed Size	7" x 20 3/8" (177 x 518 mm)	
Work Surface	2" x 21 3/32" (52 x 61mm)	2" x 31 3/16" (52 x 97mm)
Post Height	7" (178mm)	
Stitch Type	301	
Needle Gauge	Standard 1/16" (1.6 mm)	
Needle Gauges Available	1/32" to 3/16" (0.8 to 4.8mm)	

(* Speed dependent on materials, thread and operation.)

POST BED