

PREMIER BY **CONSEW** Since 1898
MODEL CN3115RB-1

WITH
CENTRAL LARGE BOBBIN
OSCILLATING SHUTTLE
LINK TAKE-UP LEVER
ROTARY STITCH CONTROL
REVERSE FEED



SINGLE NEEDLE
DROP FEED
LOCKSTITCH MACHINE

Model CN3115RB-1

APPLICATIONS

- For general utility work.
- Designed for sewing light to medium-weight materials such as cloth synthetics and leather.
- Suitable for use by tailors, drycleaners, alteration rooms, general factory work, etc.
- Designed for any lap seam felling operation including difficult-to-sew tubular products

FEATURES

- Central large bobbin
- Oscillating shuttle
- Link take-up lever
- Reverse feed
- Rotary knob stitch control

SPECIFICATIONS

Speed, Max. (S.P.M.)	1800 *	Shuttle Hook	3-15
Clearance Under Foot	1/4" (6.5mm)	Bobbin Case	3-27
Needle Bar Stroke	1 15/32" (37.4mm)	Bed Size	7" x 18 7/8" (178 x 478 mm)
Stitch Length, Max.	6 s.p.i. (4 mm)	Work Space	10 3/8" (268mm)
Needle	16 x 87	Stitch Type	301
Bobbin	Metal	3-26	
	Pre-wound	P	

* Speed depends on operation, thread and materials