

CONSEW Since 1898

MODEL CN2053R-1

HORIZONTAL AXIS TRANSVERSE ROTARY HOOK
 REVERSE FEED
 COMBINATION ZIG-ZAG AND STRAIGHT STITCHER
 BUILT-IN BOBBIN WINDER
 NEEDLE POSITION ADJUSTMENT
 METAL GEARS (HARDENED STEEL)
 ADJUSTABLE REVERSE STITCH LENGTH



Optional: Complete stand and motor.

SINGLE NEEDLE
 DROP FEED
ZIG-ZAG
 LOCKSTITCH MACHINE

ZIG ZAG

Model CN2053R-1

APPLICATIONS

- For sewing light to medium heavy weight fabrics including clothing, shoes and caps, leather articles, bags and more
- For attaching lace, elastic band, bottom hemming, edge stitching, butted seaming, applique and similar operations
- Federal stitch type 304

FEATURES

- Horizontal axis transverse rotary hook
- Dial zig-zag regulator
- Locking zig-zag width regulator
- Straight stitches when zig-zag set to "0" using straight stitch locking device
- Stitches per minute — up to 2500 *
- Reverse stitching
- Built-in bobbin winder
- Metal gears (hardened steel)
- Built-in free-hand monogramming lever



SPECIFICATIONS

Speed, Max. (S.P.M.) *	2500	Bed Size	7" x 15 11/16" (178 x 398.5 mm)
Clearance Under Foot	6/25" (6.4mm)	Work Space	8 5/16" (211 mm)
Needle Bar Stroke	1 6/25" (31.5 mm)	Stitch Width Max.	11/32" (9 mm)
Stitch Length, Max.	5 s.p.i. (5 mm)	Stitch Type	304
Needle	135 x 5		

* Speed depends on width of zig-zag, material and thread.