

Since 1898
CONSEW[®]

MODEL F-117C

FULLY AUTOMATIC BOBBIN WINDER with Digital Counter

ADJUSTABLE

**Winds small or large
capacity bobbins**

APPLICATIONS

- Perfect and accurate bobbin winding with no operator necessary.
- Types of thread wound include monofilament, nylon, rayon, cotton, synthetics and embroidery.
- Winds any type bobbin (L, G, M) with .237" or 6mm opening including HA, DB, 400W, TC, 112W and HSM types, embroidery metal bobbins.
- Ideal for sewing and embroidery thread.

ADVANTAGES

- Lower Costs - less costly than pre-wounds per bobbin and no large lot purchases necessary.
- True Color Consistency - pre-wound colors can often vary noticeably which affects sewn product quality.
- Reduced Waste/Better Inventory Control - an operator needs only one thread spool instead of two.
- All thread winding is done in a central location which ensures that the correct quantity of thread is used to do the job - NO PARTIALLY USED THREAD CONES.
- Cuts Machine Downtime - Increases Operator Production - operator-wound bobbins consume operator time.
- Guaranteed Yardage on Each Bobbin - operator-wound bobbins yardage varies. The F-117C helps you avoid run outs/seam repairs/more bobbin changes, seconds.
- Consistent Thread Tension - ensures smoother stitches and neater seams.
- Better Production Planning - CONSEW's automatic bobbin winder lets you control the amount of thread being wound which permits better production plans.

FEATURES

- Only 8 seconds to wind most bobbins.
- Hopper holds more than 100 bobbins.
- Automatic "shut-off" system when bobbin supply or thread is exhausted.
- No operator required.
- Built in circuit breaker.
- Two Thread Tension Adjustments.
- Digital counter permits you to pre-set amounts to be wound.

- NEW IMPROVED MODEL!**
- **SAVE MONEY—ELIMINATE COST OF PRE-WOUND BOBBINS**
 - **SAVE TIME—AUTOMATICALLY WINDS HUNDREDS OF BOBBINS**
 - **REDUCE WASTE**
 - **IDEAL FOR SEWING AND EMBROIDERY THREAD**



Available in 110V or 220 V

SPECIFICATIONS		
Motor	Main motor	AP-TBB 2P 40W (110V or 220V)
	Sub motor	4P 6W 110v. or 220v.
Machine dimension		410mm(W) x 290mm(D) x 285mm(H)
Measurement (Gross)		530mm(W) x 436mm(D) x 410mm(H)
Weight	Net weight	20 Kg
	Gross weight	22 Kg

Specifications subject to change without notice.

©2007 Consew USA -307

Since 1898
CONSEW[®]

CONSOLIDATED SEWING MACHINE CORP.

INDUSTRIAL SEWING & CUTTING EQUIPMENT

NEW YORK • MIAMI • LOS ANGELES • JAPAN