

CONSEW Since 1898

MODELS 315R-2 / 315RH-2 HEAVY MODEL 315RATCWL(E) with Fully Automated Functions and Electric Foot lift

WITH
AUTOMATIC LUBRICATION SYSTEM
REVERSE FEED



HIGH SPEED
SINGLE NEEDLE
DROP FEED, NEEDLE FEED
LOCKSTITCH MACHINE

Models 315R-2 / 315RH-2 HEAVY

APPLICATIONS

- For stitching light to medium weight fabric, knits, synthetics, vinyl, canvas, denim and coated and laminated material
- Suitable for attaching pockets to shirts, sewing collars and cuffs, stitching skirts, blouses, dresses, raincoats, general wearing apparel
- Model 315RH - designed for sewing medium to heavy-weight materials

FEATURES

- High speed - 5000 S.P.M. for light to medium-weight materials
4000 S.P.M. for medium to heavy-weight materials
- Horizontal axis transverse rotary hook
- Synchronized drop and needle feed assures even feeding of slippery and difficult to feed materials
- Fully automatic lubrication with recirculating pump

VERSIONS

Model 315R-2– For light to medium weight fabric

Model 315RH-2 – for medium to heavy-weight materials

Model 315RATCWL(E) – with Fully Automated Functions and Electric Foot lift (special order)

SPECIFICATIONS

MODEL	315R-2	315RH-2 Heavy
Speed, Max. (S.P.M.)	5000*	4000*
Clearance Under Foot	Hand 7/32" (5.5mm), Knee 9/16" (14mm)	Hand 7/32" (5.5mm), Knee 9/16" (14mm)
Needle Bar Stroke	1-7/32" (30.7mm)	1-3/8" (34.6mm)
Stitch Length, Max.	6.4 s.p.i. (4mm)	5 s.p.i. (5mm)
Needle	16 x 257	16 x 257
Bobbin	Metal	C-31
	Pre-wound	L
Lubrication	Fully Automatic	Fully Automatic
Hook	C-27	C-29
Bed Size	7" x 18-7/8" (178 x 479 mm)	7" x 18-7/8" (178 x 479 mm)
Work Space	10" (254 mm)	10" (254 mm)

* Depending on materials, thread and operation